



Attestation of Conformity

No. N8AUK 094747 0070 Rev. 00

Holder of Certificate: Xinsu Global Electronic Co., Limited

Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road

Central HONG KONG

Product: Switching power supply unit

(SWITCHING POWER SUPPLY/CHARGER)

This Attestation of Conformity is issued on a voluntary basis according to the Electrical Equipment (Safety) Regulations 2016 relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the regulations and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 652101912602

Date, 2021-05-31

(Richard Zhu)



After preparation of the necessary UK regulation technical documentation as well as the UK declaration of conformity the required UKCA marking can be affixed on the product. Other applicable UK regulations have to be observed.





Attestation of Conformity

No. N8AUK 094747 0070 Rev. 00

Model(s): XSGxxxyyyy L2, XSGxxxyyyyzz L2,

XSExxxyyyy L2, XSExxxyyyyzz L2, XSECxxxyyyy L2, XSECxxxyyyyzz L2

(xxx=042-730, stands for the rated output voltage from 4.2VDC to 73.0VDC; yyyy=0300-8000, stands for the rated output current from 0.3A to 8.0A; zz=AA-ZZ except MM, can be two uppercase English letters, only denotes for marketing

purpose)

Brand: Xinsu Global



Parameters:

Rated Input: 100-240VAC, 50/60Hz, 3.0A Max Rated Output: See below table for details

Protection Class: II
Degree of Protection: IP20

Model	Rated output voltage (VDC)	Rated output current (A)	Max. rated output power (W)
XSGxxxyyyy L2, XSGxxxyyyyzz L2, XSExxxyyyy L2, XSExxxyyyyzz L2, XSECxxxyyyy L2, XSECxxxyyyy L2,	4.2-12.6	0.3-8.0	100.8
	12.7-14.6	0.3-7.5	102.2
	14.7-17.2	0.3-7.5	112.5
	17.3-19.0	0.3-6.0	114.0
	19.1-22.0	0.3-6.0	120.0
	22.1-32.0	0.3-5.5	120.0
	32.1-36.5	0.3-3.0	109.5
	36.6-57.9	0.3-3.0	126.0
	58.0-58.8	0.3-2.0	117.6
	58.9-73.0	0.3-2.0	125.0

Tested EN 62368-1:2014/A11:2017 BS EN 62368-1:2014/A11:2017

Page 2 of 2

After preparation of the necessary UK regulation technical documentation as well as the UK declaration of conformity the required UKCA marking can be affixed on the product. Other applicable UK regulations have to be observed.