

Attestation of Conformity

No. N8AUK 094747 0073 Rev. 00

Holder of Certificate: **Xinsu Global Electronic Co., Limited**
Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road
Central
HONG KONG

Product: **Switching power supply unit**
(SWITCHING POWER SUPPLY/CHARGER)

This Attestation of Conformity is issued on a voluntary basis according to the Electrical Equipment (Safety) Regulations 2016 relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the regulations and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 652101711302

Date, 2021-06-07



(Richard Zhu)

Attestation of Conformity

No. N8AUK 094747 0073 Rev. 00

Model(s):

XSGxxxxxyyyyMM, XSExxxxxyyyyMM,
XSECxxxxxyyyyMM, XSGxxxxxyyyyMM,
XSExxxxxyyyyMM, XSECxxxxxyyyyMM
(xxx=042-730, which denotes the rated output
voltage from 4.2VDC to 73.0VDC; yyyy=0300-9999,
which denotes the rated output current from 300mA
to 9999mA; yyyyy=10000-11000, which denotes the
rated output current from 10000mA to 11000mA.)

Brand:

Xinsu Global

**Parameters:**

Rated Input: 100-240VAC, 50/60Hz, 3.0A Max

Rated Output: See below table for details

Protection Class: I

Degree of Protection: IP20

**Tested
according to:**

EN 62368-1:2014/A11:2017

BS EN 62368-1:2014/A11:2017

Attestation of Conformity

No. N8AUK 094747 0073 Rev. 00

Model No.	Rated output voltage (VDC)	Rated output current (mA)	Max. rated output power (W)
XSGxxxxxyyyyMM, XSExxxxxyyyyMM, XSECxxxxxyyyyMM	4.2-9.0	10000	90.0
	9.1-14.6	10000-11000	160.6
	14.7-17.0	10000	170.0
	17.1-19.0	10000	190.0
XSGxxxxxyyyyMM, XSExxxxxyyyyMM, XSECxxxxxyyyyMM	4.2-9.0	300-9999	90.0
	9.1-14.6	300-9999	146.0
	14.7-17.0	300-9999	170.0
	17.1-19.0	300-9999	190.0
	19.1-22.0	300-9500	190.0
	22.1-32.0	300-8500	205.8
	32.1-36.5	300-6000	219.0
	36.6-57.9	300-5000	210.0
	58.0-58.8	300-3600	210.2
	58.9-73.0	300-3400	204.0