



Certificate of Conformity/Approval

Certificate No.: SAA-211085-EA

Certificate Holder: Xinsu Global Electronic Co., Limited
Unit 2508A, 25/F Bank of America Tower
12 Harcourt Road
Central
Hong Kong

Regulatory Definition: Power Supply or Charger
Product Description: Switching Power Supply (Direct plug-in)
Trade Name/s: Xinsu Global
Model No.: XSG1202500 L3
Rating/Marking/s: Input: 100-240Vac 50/60Hz, 0.6A Max
Output: 12.0Vdc 2.5A 30.0W
ta:35°C, Class II

Standard/s: AS/NZS 62368.1:2018
Condition/s: For use with audio/video, information or
communication technology equipment only.

Approval Marks: RCM (In accordance with AS/NZS 4417 and EESS requirements)
and
SAA-211085-EA (In accordance with NSW legislative requirements)

Initial Issue Date: 23 June 2021
Expiry Date: 23 June 2026

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085
Page 1 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1202500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 2.5A 30.0W ta:35°C, Class II
XSG0420500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 4.2Vdc 0.5A 2.1W ta:35°C, Class II
XSG0420500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 4.2Vdc 0.5A 2.1W ta:35°C, Class II
XSG0421000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 4.2Vdc 1.0A 4.2W ta:35°C, Class II
XSG0421000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 4.2Vdc 1.0A 4.2W ta:35°C, Class II
XSG0421500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 4.2Vdc 1.5A 6.3W ta:35°C, Class II
XSG0421500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 4.2Vdc 1.5A 6.3W ta:35°C, Class II
XSG0422000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 4.2Vdc 2.0A 8.4W ta:35°C, Class II
XSG0422000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 4.2Vdc 2.0A 8.4W ta:35°C, Class II
XSG0422500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 4.2Vdc 2.5A 10.5W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 2 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG0422500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 4.2Vdc 2.5A 10.5W ta:35°C, Class II
XSG0423000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 4.2Vdc 3.0A 12.6W ta:35°C, Class II
XSG0423000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 4.2Vdc 3.0A 12.6W ta:35°C, Class II
XSG0424000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 4.2Vdc 4.0A 16.8W ta:35°C, Class II
XSG0424000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 4.2Vdc 4.0A 16.8W ta:35°C, Class II
XSG0500500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 0.5A 2.5W ta:35°C, Class II
XSG0500500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 0.5A 2.5W ta:35°C, Class II
XSG0501000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 1.0A 5.0W ta:35°C, Class II
XSG0501000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 1.0A 5.0W ta:35°C, Class II
XSG0501200 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 1.2A 6.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 3 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG0501200AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 1.2A 6.0W ta:35°C, Class II
XSG0501500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 1.5A 7.5W ta:35°C, Class II
XSG0501500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 1.5A 7.5W ta:35°C, Class II
XSG0502000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 2.0A 10.0W ta:35°C, Class II
XSG0502000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 2.0A 10.0W ta:35°C, Class II
XSG0502100 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 2.1A 10.5W ta:35°C, Class II
XSG0502100AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 2.1A 10.5W ta:35°C, Class II
XSG0502500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 2.5A 12.5W ta:35°C, Class II
XSG0502500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 2.5A 12.5W ta:35°C, Class II
XSG0503000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 3.0A 15.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 4 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG0503000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 3.0A 15.0W ta:35°C, Class II
XSG0503500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 3.5A 17.5W ta:35°C, Class II
XSG0503500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 3.5A 17.5W ta:35°C, Class II
XSG0504000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 4.0A 20.0W ta:35°C, Class II
XSG0504000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 5.0Vdc 4.0A 20.0W ta:35°C, Class II
XSG0600500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 0.5A 3.0W ta:35°C, Class II
XSG0600500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 0.5A 3.0W ta:35°C, Class II
XSG0600600 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 0.6A 3.6W ta:35°C, Class II
XSG0600600AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 0.6A 3.6W ta:35°C, Class II
XSG0601000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 1.0A 6.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 5 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG0601000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 1.0A 6.0W ta:35°C, Class II
XSG0601500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 1.5A 9.0W ta:35°C, Class II
XSG0601500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 1.5A 9.0W ta:35°C, Class II
XSG0602000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 2.0A 12.0W ta:35°C, Class II
XSG0602000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 2.0A 12.0W ta:35°C, Class II
XSG0602500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 2.5A 15.0W ta:35°C, Class II
XSG0602500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 2.5A 15.0W ta:35°C, Class II
XSG0603000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 3.0A 18.0W ta:35°C, Class II
XSG0603000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 3.0A 18.0W ta:35°C, Class II
XSG0603500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 3.5A 21.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 6 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG0603500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 3.5A 21.0W ta:35°C, Class II
XSG0604000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 4.0A 24.0W ta:35°C, Class II
XSG0604000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.0Vdc 4.0A 24.0W ta:35°C, Class II
XSG0650300 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 0.3A 2.0W ta:35°C, Class II
XSG0650300AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 0.3A 2.0W ta:35°C, Class II
XSG0650400 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 0.4A 2.6W ta:35°C, Class II
XSG0650400AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 0.4A 2.6W ta:35°C, Class II
XSG0650500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 0.5A 3.3W ta:35°C, Class II
XSG0650500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 0.5A 3.3W ta:35°C, Class II
XSG0651000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 1.0A 6.5W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 7 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG0651000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 1.0A 6.5W ta:35°C, Class II
XSG0651500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 1.5A 9.8W ta:35°C, Class II
XSG0651500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 1.5A 9.8W ta:35°C, Class II
XSG0652000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 2.0A 13.0W ta:35°C, Class II
XSG0652000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 2.0A 13.0W ta:35°C, Class II
XSG0652500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 2.5A 16.3W ta:35°C, Class II
XSG0652500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 2.5A 16.3W ta:35°C, Class II
XSG0653000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 3.0A 19.5W ta:35°C, Class II
XSG0653000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 3.0A 19.5W ta:35°C, Class II
XSG0653500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 3.5A 22.8W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 8 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG0653500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 6.5Vdc 3.5A 22.8W ta:35°C, Class II
XSG0730500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.3Vdc 0.5A 3.7W ta:35°C, Class II
XSG0730500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.3Vdc 0.5A 3.7W ta:35°C, Class II
XSG0731000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.3Vdc 1.0A 7.3W ta:35°C, Class II
XSG0731000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.3Vdc 1.0A 7.3W ta:35°C, Class II
XSG0731500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.3Vdc 1.5A 11.0W ta:35°C, Class II
XSG0731500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.3Vdc 1.5A 11.0W ta:35°C, Class II
XSG0732000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.3Vdc 2.0A 14.6W ta:35°C, Class II
XSG0732000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.3Vdc 2.0A 14.6W ta:35°C, Class II
XSG0732500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.3Vdc 2.5A 18.3W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 9 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG0732500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.3Vdc 2.5A 18.3W ta:35°C, Class II
XSG0733000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.3Vdc 3.0A 21.9W ta:35°C, Class II
XSG0733000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.3Vdc 3.0A 21.9W ta:35°C, Class II
XSG0750500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.5Vdc 0.5A 3.8W ta:35°C, Class II
XSG0750500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.5Vdc 0.5A 3.8W ta:35°C, Class II
XSG0750800 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.5Vdc 0.8A 6.0W ta:35°C, Class II
XSG0750800AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.5Vdc 0.8A 6.0W ta:35°C, Class II
XSG0751000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.5Vdc 1.0A 7.5W ta:35°C, Class II
XSG0751000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.5Vdc 1.0A 7.5W ta:35°C, Class II
XSG0751500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.5Vdc 1.5A 11.3W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 10 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG0751500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.5Vdc 1.5A 11.3W ta:35°C, Class II
XSG0752000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.5Vdc 2.0A 15.0W ta:35°C, Class II
XSG0752000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.5Vdc 2.0A 15.0W ta:35°C, Class II
XSG0752500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.5Vdc 2.5A 18.8W ta:35°C, Class II
XSG0752500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.5Vdc 2.5A 18.8W ta:35°C, Class II
XSG0753000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.5Vdc 3.0A 22.5W ta:35°C, Class II
XSG0753000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 7.5Vdc 3.0A 22.5W ta:35°C, Class II
XSG0840500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 0.5A 4.2W ta:35°C, Class II
XSG0840500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 0.5A 4.2W ta:35°C, Class II
XSG0841000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 1.0A 8.4W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 11 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG0841000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 1.0A 8.4W ta:35°C, Class II
XSG0841200 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 1.2A 10.1W ta:35°C, Class II
XSG0841200AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 1.2A 10.1W ta:35°C, Class II
XSG0841500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 1.5A 12.6W ta:35°C, Class II
XSG0841500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 1.5A 12.6W ta:35°C, Class II
XSG0841800 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 1.8A 15.1W ta:35°C, Class II
XSG0841800AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 1.8A 15.1W ta:35°C, Class II
XSG0842000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 2.0A 16.8W ta:35°C, Class II
XSG0842000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 2.0A 16.8W ta:35°C, Class II
XSG0842500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 2.5 A21.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 12 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG0842500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 2.5A 21.0W ta:35°C, Class II
XSG0843000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 3.0A 25.2W ta:35°C, Class II
XSG0843000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 8.4Vdc 3.0A 25.2W ta:35°C, Class II
XSG0900300 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 0.3A 2.7W ta:35°C, Class II
XSG0900300AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 0.3A 2.7W ta:35°C, Class II
XSG0900500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 0.5A 4.5W ta:35°C, Class II
XSG0900500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 0.5A 4.5W ta:35°C, Class II
XSG0900600 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 0.6A 5.4W ta:35°C, Class II
XSG0900600AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 0.6A 5.4W ta:35°C, Class II
XSG0901000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 1.0A 9.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 13 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG0901000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 1.0A 9.0W ta:35°C, Class II
XSG0901200 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 1.2A 10.8W ta:35°C, Class II
XSG0901200AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 1.2A 10.8W ta:35°C, Class II
XSG0901500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 1.5A 13.5W ta:35°C, Class II
XSG0901500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 1.5A 13.5W ta:35°C, Class II
XSG0902000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 2.0A 18.0W ta:35°C, Class II
XSG0902000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 2.0A 18.0W ta:35°C, Class II
XSG0902500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 2.5A 22.5W ta:35°C, Class II
XSG0902500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 9.0Vdc 2.5A 22.5W ta:35°C, Class II
XSG1000500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 10.0Vdc 0.5A 5.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 14 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1000500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 10.0Vdc 0.5A 5.0W ta:35°C, Class II
XSG1001000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 10.0Vdc 1.0A 10.0W ta:35°C, Class II
XSG1001000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 10.0Vdc 1.0A 10.0W ta:35°C, Class II
XSG1001500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 10.0Vdc 1.5A 15.0W ta:35°C, Class II
XSG1001500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 10.0Vdc 1.5A 15.0W ta:35°C, Class II
XSG1002000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 10.0Vdc 2.0A 20.0W ta:35°C, Class II
XSG1002000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 10.0Vdc 2.0A 20.0W ta:35°C, Class II
XSG1002500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 10.0Vdc 2.5A 25.0W ta:35°C, Class II
XSG1002500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 10.0Vdc 2.5A 25.0W ta:35°C, Class II
XSG1100500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 11.0Vdc 0.5A 5.5W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 15 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1100500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 11.0Vdc 0.5A 5.5W ta:35°C, Class II
XSG1101000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 11.0Vdc 1.0A 11.0W ta:35°C, Class II
XSG1101000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 11.0Vdc 1.0A 11.0W ta:35°C, Class II
XSG1101500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 11.0Vdc 1.5A 16.5W ta:35°C, Class II
XSG1101500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 11.0Vdc 1.5A 16.5W ta:35°C, Class II
XSG1102000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 11.0Vdc 2.0A 22.0W ta:35°C, Class II
XSG1102000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 11.0Vdc 2.0A 22.0W ta:35°C, Class II
XSG1102500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 11.0Vdc 2.5A 27.5W ta:35°C, Class II
XSG1102500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 11.0Vdc 2.5A 27.5W ta:35°C, Class II
XSG1112700 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 11.1Vdc 2.7A 30.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 16 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1112700AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 11.1Vdc 2.7A 30.0W ta:35°C, Class II
XSG1200300 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 0.3A 3.6W ta:35°C, Class II
XSG1200300AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 0.3A 3.6W ta:35°C, Class II
XSG1200400 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 0.4A 4.8W ta:35°C, Class II
XSG1200400AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 0.4A 4.8W ta:35°C, Class II
XSG1200500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 0.5A 6.0W ta:35°C, Class II
XSG1200500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 0.5A 6.0W ta:35°C, Class II
XSG1200600 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 0.6A 7.2W ta:35°C, Class II
XSG1200600AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 0.6A 7.2W ta:35°C, Class II
XSG1200700 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 0.7A 8.4W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 17 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1200700AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 0.7A 8.4W ta:35°C, Class II
XSG1200800 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 0.8A 9.6W ta:35°C, Class II
XSG1200800AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 0.8A 9.6W ta:35°C, Class II
XSG1200900 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 0.9A 10.8W ta:35°C, Class II
XSG1200900AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 0.9A 10.8W ta:35°C, Class II
XSG1201000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 1.0A 12.0W ta:35°C, Class II
XSG1201000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 1.0A 12.0W ta:35°C, Class II
XSG1201250 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 1.25A 15.0W ta:35°C, Class II
XSG1201250AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 1.25A 15.0W ta:35°C, Class II
XSG1201500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 1.5A 18.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 18 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1201500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 1.5A 18.0W ta:35°C, Class II
XSG1201750 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 1.75 A21.0W ta:35°C, Class II
XSG1201750AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 1.75 A21.0W ta:35°C, Class II
XSG1202000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 2.0A 24.0W ta:35°C, Class II
XSG1202000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.0Vdc 2.0A 24.0W ta:35°C, Class II
XSG1260500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.6Vdc 0.5A 6.3W ta:35°C, Class II
XSG1260500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.6Vdc 0.5A 6.3W ta:35°C, Class II
XSG1261000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.6Vdc 1.0A 12.6W ta:35°C, Class II
XSG1261000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.6Vdc 1.0A 12.6W ta:35°C, Class II
XSG1261200 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.6Vdc 1.2A 15.1W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 19 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1261200AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.6Vdc 1.2A 15.1W ta:35°C, Class II
XSG1261500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.6Vdc 1.5A 18.9W ta:35°C, Class II
XSG1261500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.6Vdc 1.5A 18.9W ta:35°C, Class II
XSG1261800 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.6Vdc 1.8A 22.7W ta:35°C, Class II
XSG1261800AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.6Vdc 1.8A 22.7W ta:35°C, Class II
XSG1262000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.6Vdc 2.0A 25.2W ta:35°C, Class II
XSG1262000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.6Vdc 2.0A 25.2W ta:35°C, Class II
XSG1282340 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.8Vdc 2.34A 29.95W ta:35°C, Class II
XSG1282340AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 12.8Vdc 2.34A 29.95W ta:35°C, Class II
XSG1300500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.0Vdc 0.5A 6.5W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 20 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1300500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.0Vdc 0.5A 6.5W ta:35°C, Class II
XSG1301000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.0Vdc 1.0A 13.0W ta:35°C, Class II
XSG1301000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.0Vdc 1.0A 13.0W ta:35°C, Class II
XSG1301500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.0Vdc 1.5A 19.5W ta:35°C, Class II
XSG1301500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.0Vdc 1.5A 19.5W ta:35°C, Class II
XSG1302000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.0Vdc 2.0A 26.0W ta:35°C, Class II
XSG1302000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.0Vdc 2.0A 26.0W ta:35°C, Class II
XSG1350500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.5Vdc 0.5A 6.8W ta:35°C, Class II
XSG1350500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.5Vdc 0.5A 6.8W ta:35°C, Class II
XSG1351000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.5Vdc 1.0A 13.5W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 21 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1351000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.5Vdc 1.0A 13.5W ta:35°C, Class II
XSG1351500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.5Vdc 1.5A 20.3W ta:35°C, Class II
XSG1351500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.5Vdc 1.5A 20.3W ta:35°C, Class II
XSG1352000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.5Vdc 2.0A 27.0W ta:35°C, Class II
XSG1352000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 13.5Vdc 2.0A 27.0W ta:35°C, Class II
XSG1400500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.0Vdc 0.5A 7.0W ta:35°C, Class II
XSG1400500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.0Vdc 0.5A 7.0W ta:35°C, Class II
XSG1401000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.0Vdc 1.0A 14.0W ta:35°C, Class II
XSG1401000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.0Vdc 1.0A 14.0W ta:35°C, Class II
XSG1401200 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.0Vdc 1.2A 16.8W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 22 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1401200AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.0Vdc 1.2A 16.8W ta:35°C, Class II
XSG1401500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.0Vdc 1.5A 21.0W ta:35°C, Class II
XSG1401500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.0Vdc 1.5A 21.0W ta:35°C, Class II
XSG1402000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.0Vdc 2.0A 28.0W ta:35°C, Class II
XSG1402000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.0Vdc 2.0A 28.0W ta:35°C, Class II
XSG1460500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.6Vdc 0.5A 7.3W ta:35°C, Class II
XSG1460500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.6Vdc 0.5A 7.3W ta:35°C, Class II
XSG1460800 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.6Vdc 0.8A 11.7W ta:35°C, Class II
XSG1460800AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.6Vdc 0.8A 11.7W ta:35°C, Class II
XSG1461000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.6Vdc 1.0A 14.6W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 23 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1461000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.6Vdc 1.0A 14.6W ta:35°C, Class II
XSG1461500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.6Vdc 1.5A 21.9W ta:35°C, Class II
XSG1461500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.6Vdc 1.5A 21.9W ta:35°C, Class II
XSG1461750 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.6Vdc 1.75A 25.6W ta:35°C, Class II
XSG1461750AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 14.6Vdc 1.75A 25.6W ta:35°C, Class II
XSG1500300 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 15.0Vdc 0.3A 4.5W ta:35°C, Class II
XSG1500300AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 15.0Vdc 0.3A 4.5W ta:35°C, Class II
XSG1500500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 15.0Vdc 0.5A 7.5W ta:35°C, Class II
XSG1500500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 15.0Vdc 0.5A 7.5W ta:35°C, Class II
XSG1500800 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 15.0Vdc 0.8A 12.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 24 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1500800AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 15.0Vdc 0.8A 12.0W ta:35°C, Class II
XSG1501000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 15.0Vdc 1.0A 15.0W ta:35°C, Class II
XSG1501000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 15.0Vdc 1.0A 15.0W ta:35°C, Class II
XSG1501200 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 15.0Vdc 1.2A 18.0W ta:35°C, Class II
XSG1501200AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 15.0Vdc 1.2A 18.0W ta:35°C, Class II
XSG1501500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 15.0Vdc 1.5A 22.5W ta:35°C, Class II
XSG1501500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 15.0Vdc 1.5A 22.5W ta:35°C, Class II
XSG1501750 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 15.0Vdc 1.75A 26.3W ta:35°C, Class II
XSG1501750AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 15.0Vdc 1.75A 26.3W ta:35°C, Class II
XSG1600500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.0Vdc 0.5A 8.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 25 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1600500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.0Vdc 0.5A 8.0W ta:35°C, Class II
XSG1601000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.0Vdc 1.0A 16.0W ta:35°C, Class II
XSG1601000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.0Vdc 1.0A 16.0W ta:35°C, Class II
XSG1601500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.0Vdc 1.5A 24.0W ta:35°C, Class II
XSG1601500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.0Vdc 1.5A 24.0W ta:35°C, Class II
XSG1620500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.2Vdc 0.5A 8.1W ta:35°C, Class II
XSG1620500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.2Vdc 0.5A 8.1W ta:35°C, Class II
XSG1621000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.2Vdc 1.0A 16.2W ta:35°C, Class II
XSG1621000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.2Vdc 1.0A 16.2W ta:35°C, Class II
XSG1621500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.2Vdc 1.5A 24.3W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 26 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1621500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.2Vdc 1.5A 24.3W ta:35°C, Class II
XSG1680500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.8Vdc 0.5A 8.4W ta:35°C, Class II
XSG1680500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.8Vdc 0.5A 8.4W ta:35°C, Class II
XSG1681000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.8Vdc 1.0A 16.8W ta:35°C, Class II
XSG1681000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.8Vdc 1.0A 16.8W ta:35°C, Class II
XSG1681200 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.8Vdc 1.2A 20.2W ta:35°C, Class II
XSG1681200AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.8Vdc 1.2A 20.2W ta:35°C, Class II
XSG1681500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.8Vdc 1.5A 25.2W ta:35°C, Class II
XSG1681500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 16.8Vdc 1.5A 25.2W ta:35°C, Class II
XSG1800500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.0Vdc 0.5A 9.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 27 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1800500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.0Vdc 0.5A 9.0W ta:35°C, Class II
XSG1800600 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.0Vdc 0.6A 10.8W ta:35°C, Class II
XSG1800600AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.0Vdc 0.6A 10.8W ta:35°C, Class II
XSG1800700 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.0Vdc 0.7A 12.6W ta:35°C, Class II
XSG1800700AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.0Vdc 0.7A 12.6W ta:35°C, Class II
XSG1801000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.0Vdc 1.0A 18.0W ta:35°C, Class II
XSG1801000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.0Vdc 1.0A 18.0W ta:35°C, Class II
XSG1801500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.0Vdc 1.5A 27.0W ta:35°C, Class II
XSG1801500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.0Vdc 1.5A 27.0W ta:35°C, Class II
XSG1830500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.3Vdc 0.5A 9.2W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 28 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1830500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.3Vdc 0.5A 9.2W ta:35°C, Class II
XSG1831000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.3Vdc 1.0A 18.3W ta:35°C, Class II
XSG1831000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.3Vdc 1.0A 18.3W ta:35°C, Class II
XSG1831250 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.3Vdc 1.25A 22.9W ta:35°C, Class II
XSG1831250AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 18.3Vdc 1.25A 22.9W ta:35°C, Class II
XSG1950500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 19.5Vdc 0.5A 9.8W ta:35°C, Class II
XSG1950500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 19.5Vdc 0.5A 9.8W ta:35°C, Class II
XSG1951000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 19.5Vdc 1.0A 19.5W ta:35°C, Class II
XSG1951000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 19.5Vdc 1.0A 19.5W ta:35°C, Class II
XSG1951250 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 19.5Vdc 1.25A 24.4W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 29 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG1951250AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 19.5Vdc 1.25A 24.4W ta:35°C, Class II
XSG2000500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 20.0Vdc 0.5A 10.0W ta:35°C, Class II
XSG2000500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 20.0Vdc 0.5A 10.0W ta:35°C, Class II
XSG2001000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 20.0Vdc 1.0A 20.0W ta:35°C, Class II
XSG2001000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 20.0Vdc 1.0A 20.0W ta:35°C, Class II
XSG2001250 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 20.0Vdc 1.25A 25.0W ta:35°C, Class II
XSG2001250AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 20.0Vdc 1.25A 25.0W ta:35°C, Class II
XSG2001500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 20.0Vdc 1.5A 30.0W ta:35°C, Class II
XSG2001500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 20.0Vdc 1.5A 30.0W ta:35°C, Class II
XSG2100500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 21.0Vdc 0.5A 10.5W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 30 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG2100500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 21.0Vdc 0.5A 10.5W ta:35°C, Class II
XSG2100600 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 21.0Vdc 0.6A 12.6W ta:35°C, Class II
XSG2100600AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 21.0Vdc 0.6A 12.6W ta:35°C, Class II
XSG2101000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 21.0Vdc 1.0A 21.0W ta:35°C, Class II
XSG2101000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 21.0Vdc 1.0A 21.0W ta:35°C, Class II
XSG2101200 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 21.0Vdc 1.2A 25.2W ta:35°C, Class II
XSG2101200AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 21.0Vdc 1.2A 25.2W ta:35°C, Class II
XSG2101420 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 21.0Vdc 1.42A 29.8W ta:35°C, Class II
XSG2101420AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 21.0Vdc 1.42A 29.8W ta:35°C, Class II
XSG2200500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.0Vdc 0.5A 11.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 31 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG2200500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.0Vdc 0.5A 11.0W ta:35°C, Class II
XSG2201000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.0Vdc 1.0A 22.0W ta:35°C, Class II
XSG2201000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.0Vdc 1.0A 22.0W ta:35°C, Class II
XSG2201200 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.0Vdc 1.2A 26.4W ta:35°C, Class II
XSG2201200AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.0Vdc 1.2A 26.4W ta:35°C, Class II
XSG2250500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.5Vdc 0.5A 11.3W ta:35°C, Class II
XSG2250500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.5Vdc 0.5A 11.3W ta:35°C, Class II
XSG2250600 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.5Vdc 0.6A 13.5W ta:35°C, Class II
XSG2250600AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.5Vdc 0.6A 13.5W ta:35°C, Class II
XSG2250800 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.5Vdc 0.8A 18.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 32 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG2250800AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.5Vdc 0.8A 18.0W ta:35°C, Class II
XSG2251000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.5Vdc 1.0A 22.5W ta:35°C, Class II
XSG2251000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.5Vdc 1.0A 22.5W ta:35°C, Class II
XSG2251200 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.5Vdc 1.2A 27.0W ta:35°C, Class II
XSG2251200AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 22.5Vdc 1.2A 27.0W ta:35°C, Class II
XSG2400300 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 0.3A 7.2W ta:35°C, Class II
XSG2400300AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 0.3A 7.2W ta:35°C, Class II
XSG2400380 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 0.38A 9.1W ta:35°C, Class II
XSG2400380AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 0.38A 9.1W ta:35°C, Class II
XSG2400500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 0.5A 12.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 33 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG2400500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 0.5A 12.0W ta:35°C, Class II
XSG2400600 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 0.6A 14.4W ta:35°C, Class II
XSG2400600AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 0.6A 14.4W ta:35°C, Class II
XSG2400800 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 0.8A 19.2W ta:35°C, Class II
XSG2400800AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 0.8A 19.2W ta:35°C, Class II
XSG2401000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 1.0A 24.0W ta:35°C, Class II
XSG2401000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 1.0A 24.0W ta:35°C, Class II
XSG2401200 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 1.2A 28.8W ta:35°C, Class II
XSG2401200AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 1.2A 28.8W ta:35°C, Class II
XSG2401250 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 1.25A 30.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 34 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG2401250AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 24.0Vdc 1.25A 30.0W ta:35°C, Class II
XSG2520500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 25.2Vdc 0.5A 12.6W ta:35°C, Class II
XSG2520500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 25.2Vdc 0.5A 12.6W ta:35°C, Class II
XSG2521000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 25.2Vdc 1.0A 25.2W ta:35°C, Class II
XSG2521000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 25.2Vdc 1.0A 25.2W ta:35°C, Class II
XSG2550500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 25.5Vdc 0.5A 12.8W ta:35°C, Class II
XSG2550500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 25.5Vdc 0.5A 12.8W ta:35°C, Class II
XSG2551000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 25.5Vdc 1.0A 25.5W ta:35°C, Class II
XSG2551000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 25.5Vdc 1.0A 25.5W ta:35°C, Class II
XSG2700500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 27.0Vdc 0.5A 13.5W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 35 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG2700500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 27.0Vdc 0.5A 13.5W ta:35°C, Class II
XSG2701000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 27.0Vdc 1.0A 27.0W ta:35°C, Class II
XSG2701000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 27.0Vdc 1.0A 27.0W ta:35°C, Class II
XSG2800500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 28.0Vdc 0.5A 14.0W ta:35°C, Class II
XSG2800500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 28.0Vdc 0.5A 14.0W ta:35°C, Class II
XSG2801000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 28.0Vdc 1.0A 28.0W ta:35°C, Class II
XSG2801000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 28.0Vdc 1.0A 28.0W ta:35°C, Class II
XSG2900500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.0Vdc 0.5A 14.5W ta:35°C, Class II
XSG2900500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.0Vdc 0.5A 14.5W ta:35°C, Class II
XSG2901000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.0Vdc 1.0A 29.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 36 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG2901000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.0Vdc 1.0A 29.0W ta:35°C, Class II
XSG2920300 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.2Vdc 0.3A 8.8W ta:35°C, Class II
XSG2920300AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.2Vdc 0.3A 8.8W ta:35°C, Class II
XSG2920400 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.2Vdc 0.4A 11.7W ta:35°C, Class II
XSG2920400AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.2Vdc 0.4A 11.7W ta:35°C, Class II
XSG2920500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.2Vdc 0.5A 14.6W ta:35°C, Class II
XSG2920500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.2Vdc 0.5A 14.6W ta:35°C, Class II
XSG2921000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.2Vdc 1.0A 29.2W ta:35°C, Class II
XSG2921000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.2Vdc 1.0A 29.2W ta:35°C, Class II
XSG2940500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.4Vdc 0.5A 14.7W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 37 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG2940500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.4Vdc 0.5A 14.7W ta:35°C, Class II
XSG2941000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.4Vdc 1.0A 29.4W ta:35°C, Class II
XSG2941000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 29.4Vdc 1.0A 29.4W ta:35°C, Class II
XSG3000500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 30.0Vdc 0.5A 15.0W ta:35°C, Class II
XSG3000500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 30.0Vdc 0.5A 15.0W ta:35°C, Class II
XSG3001000 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 30.0Vdc 1.0A 30.0W ta:35°C, Class II
XSG3001000AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 30.0Vdc 1.0A 30.0W ta:35°C, Class II
XSG3200500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 32.0Vdc 0.5A 16.0W ta:35°C, Class II
XSG3200500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 32.0Vdc 0.5A 16.0W ta:35°C, Class II
XSG3200900 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 32.0Vdc 0.9A 28.8W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 38 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG3200900AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 32.0Vdc 0.9A 28.8W ta:35°C, Class II
XSG3300500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 33.0Vdc 0.5A 16.5W ta:35°C, Class II
XSG3300500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 33.0Vdc 0.5A 16.5W ta:35°C, Class II
XSG3300800 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 33.0Vdc 0.8A 26.4W ta:35°C, Class II
XSG3300800AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 33.0Vdc 0.8A 26.4W ta:35°C, Class II
XSG3300900 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 33.0Vdc 0.9A 29.7W ta:35°C, Class II
XSG3300900AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 33.0Vdc 0.9A 29.7W ta:35°C, Class II
XSG3360500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 33.6Vdc 0.5A 16.8W ta:35°C, Class II
XSG3360500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 33.6Vdc 0.5A 16.8W ta:35°C, Class II
XSG3360800 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 33.6Vdc 0.8A 26.9W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 39 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG3360800AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 33.6Vdc 0.8A 26.9W ta:35°C, Class II
XSG3400500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 34.0Vdc 0.5A 17.0W ta:35°C, Class II
XSG3400500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 34.0Vdc 0.5A 17.0W ta:35°C, Class II
XSG3400800 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 34.0Vdc 0.8A 27.2W ta:35°C, Class II
XSG3400800AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 34.0Vdc 0.8A 27.2W ta:35°C, Class II
XSG3500500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 35.0Vdc 0.5A 17.5W ta:35°C, Class II
XSG3500500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 35.0Vdc 0.5A 17.5W ta:35°C, Class II
XSG3500800 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 35.0Vdc 0.8A 28.0W ta:35°C, Class II
XSG3500800AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 35.0Vdc 0.8A 28.0W ta:35°C, Class II
XSG3600300 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 36.0Vdc 0.3A 10.8W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 40 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG3600300AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 36.0Vdc 0.3A 10.8W ta:35°C, Class II
XSG3600500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 36.0Vdc 0.5A 18.0W ta:35°C, Class II
XSG3600500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 36.0Vdc 0.5A 18.0W ta:35°C, Class II
XSG3600800 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 36.0Vdc 0.8A 28.8W ta:35°C, Class II
XSG3600800AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 36.0Vdc 0.8A 28.8W ta:35°C, Class II
XSG3780500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 37.8Vdc 0.5A 18.9W ta:35°C, Class II
XSG3780500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 37.8Vdc 0.5A 18.9W ta:35°C, Class II
XSG3780700 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 37.8Vdc 0.7A 26.5W ta:35°C, Class II
XSG3780700AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 37.8Vdc 0.7A 26.5W ta:35°C, Class II
XSG4020500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 40.2Vdc 0.5A 20.1W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 41 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG4020500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 40.2Vdc 0.5A 20.1W ta:35°C, Class II
XSG4020700 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 40.2Vdc 0.7A 28.1W ta:35°C, Class II
XSG4020700AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 40.2Vdc 0.7A 28.1W ta:35°C, Class II
XSG4200500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 42.0Vdc 0.5A 21.0W ta:35°C, Class II
XSG4200500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 42.0Vdc 0.5A 21.0W ta:35°C, Class II
XSG4200700 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 42.0Vdc 0.7A 29.4W ta:35°C, Class II
XSG4200700AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 42.0Vdc 0.7A 29.4W ta:35°C, Class II
XSG4250500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 42.5Vdc 0.5A 21.3W ta:35°C, Class II
XSG4250500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 42.5Vdc 0.5A 21.3W ta:35°C, Class II
XSG4250700 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 42.5Vdc 0.7A 29.8W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 42 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG4250700AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 42.5Vdc 0.7A 29.8W ta:35°C, Class II
XSG4300500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 43.0Vdc 0.5A 21.5W ta:35°C, Class II
XSG4300500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 43.0Vdc 0.5A 21.5W ta:35°C, Class II
XSG4300600 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 43.0Vdc 0.6A 25.8W ta:35°C, Class II
XSG4300600AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 43.0Vdc 0.6A 25.8W ta:35°C, Class II
XSG4380500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 43.8Vdc 0.5A 21.9W ta:35°C, Class II
XSG4380500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 43.8Vdc 0.5A 21.9W ta:35°C, Class II
XSG4380600 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 43.8Vdc 0.6A 26.3W ta:35°C, Class II
XSG4380600AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 43.8Vdc 0.6A 26.3W ta:35°C, Class II
XSG4400500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 44.0Vdc 0.5A 22.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 43 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG4400500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 44.0Vdc 0.5A 22.0W ta:35°C, Class II
XSG4400600 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 44.0Vdc 0.6A 26.4W ta:35°C, Class II
XSG4400600AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 44.0Vdc 0.6A 26.4W ta:35°C, Class II
XSG4500500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 45.0Vdc 0.5A 22.5W ta:35°C, Class II
XSG4500500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 45.0Vdc 0.5A 22.5W ta:35°C, Class II
XSG4600600 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 46.0Vdc 0.6A 27.6W ta:35°C, Class II
XSG4600600AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 46.0Vdc 0.6A 27.6W ta:35°C, Class II
XSG4620500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 46.2Vdc 0.5A 23.1W ta:35°C, Class II
XSG4620500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 46.2Vdc 0.5A 23.1W ta:35°C, Class II
XSG4620600 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 46.2Vdc 0.6A 27.7W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 44 of 45



A P P R O V A L S ®

Certificate of Conformity/Approval

Additional Models	Trade Name	Rating/Marking
XSG4620600AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 46.2Vdc 0.6A 27.7W ta:35°C, Class II
XSG4800300 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.3A 14.4W ta:35°C, Class II
XSG4800300AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.3A 14.4W ta:35°C, Class II
XSG4800500 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.5A 24.0W ta:35°C, Class II
XSG4800500AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.5A 24.0W ta:35°C, Class II
XSG4800600 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.6A 28.8W ta:35°C, Class II
XSG4800600AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.6A 28.8W ta:35°C, Class II
XSG4800625 L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.625A 30.0W ta:35°C, Class II
XSG4800625AU L3	Xinsu Global	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.625A 30.0W ta:35°C, Class II

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-06-21 211085

Page 45 of 45