


Xinsu Global



Xinsu Global Electronic Co.,Ltd

深圳市鑫粟國際電子有限公司



IEC60950 IEC60335 IEC61558

www.xinsuglobal.com



About us / 公司簡介



- Established in 2007.
- China Quality Manufacturer.
- ISO9001 Quality System Factory.
- Business scope: Power Adapter /Switching Power Supply /Battery Charger/ ODM&OEM
- Annual Production Value: 30,000,000USD.
- Annual Production capacity: 5000,000 Sets.
- Main Export Markets: Europe, North America, Japan, Australia, Middle East, United Kingdom, Korea, China.
- Production Staff: 150 ;R&D: 7 .
- Workshop: 3000 square meters.
- Lead time: 15-20 days depends on order quantity.
- Certifications: UL, cUL, FCC, PSE, CCC, CE, CB, TUV/GS, LVD, EMC, KC, RCM, SAA, C-Tick, PSB,ROHS.
- Main Clients: TESCO, BOSCH, HONEYWELL, SUMITOMO.ETC.

- 創建於2007年。
- 中國優質供應商。
- ISO9001品質管制體系認證工廠。
- 經營範圍：電源適配器/開關電源/電池充電器/定制類電源。
- 年銷售額:30,000,000USD 。
- 年產量:5000,000套 。
- 主要市場:歐洲,北美, 日本, 澳洲, 中東, 英國, 韓國, 中國。
- 公司員工:150人,研發:7人。
- 生產車間: 3000平方米。
- 生產交期:15-20天。
- 認證: UL, cUL, FCC, PSE, CCC, CE, CB, TUV/GS, LVD, EMC, KC, RCM, SAA, C-Tick, PSB,ROHS。
- 主要客戶:TESCO, BOSCH, HONEYWELL, SUMITOMO.ETC。



- Xinsu products are designed by the United States.
 - All models with output range 3W-210W ; to meet the needs of different users.
 - Xinsu products with international quality standards, have been certified by UL, cUL, FCC, GS, CE, PSE, SAA, RCM, C-tick , KC, CCC and ROHS.
 - Take the lead in importing DOE level VI.
 - The safety and power components are purchased from qualified agent or original factory, which make sure the materials to go through the proper channels.
 - Regularly checking the incoming materials and online products can verify the products' stability and normative.
 - The strict and scientific management ensures the good product percent of pass is 99.9%.
 - Xinsu have experience to co-operate with a number of major manufactures and Top 500 companies.
 - Xinsu have independent R & D capability of new products and launch 2~5 new products every year.
 - General sample: lead time 3days.
 - Delivery time: all the main materials have the corresponding inventory, the delivery time of the rush order is 7workdays, and the general order is 14 workdays.
 - The products can be labeled your corporate LOGO, which is conducive to your brand promotion and publicity.
 - After-sales service: One satisfaction survey every year at least, exception handling: 24 hours for short-term one, 48 hours for long-term one.
 - Good relations with freight forwarders help saving money and shipping, to be win-win.
 - Xinsu have the Import-export rights, time-saving and convenient customs clearance.
 - Abundant experience in cooperating with various merchants, help customers to get the certificates quickly and frugally through the cooperation with many large laboratories.
 - Multiple payment terms supported.
-
- 美國設計，中國製造
 - 3W-210W電源，滿足不同客戶需求。
 - 嚴格貫徹國際品質管制體系ISO9001，產品通過認證。
UL, cUL, FCC, GS, CE, PSE, SAA, RCM, C-tick , KC, CCC and ROHS.
 - 領先於市場革新技術，滿足最新六級能耗標準。
 - 安全部件等原材料採購于原廠或授權代理商等正規管道。
 - 定期檢驗來料及產線產品，驗證產品穩定性及高品質。
 - 嚴謹科學的管理確保產品合格率高於99.9%。
 - 鑫粟通過與數家世界500強企業合作積累了豐富的工作經驗。
 - 鑫粟有獨立的研發團隊，每年有2-5款新產品面世。
 - 样品交期： 3天。
 - 生產週期：加工複雜，交期長的零配件均備有庫存，極大縮短了產品週期，急單7天可出貨，一般不超過14天。
 - 產品可加印客戶logo，以便於客戶宣傳和推廣自己的品牌。
 - 售後服務：產品質保三年；每年進行至少一次滿意度調查；24小時快速反應。
 - 與多家貨代保持長期合作關係，可根據客戶需求，選擇不同運輸方式。
 - 鑫粟有進出口經營權，可加快清關及出貨進度。
 - 與多家大型實驗室密切合作，幫助客戶快速拿到證書。
 - 支持多種付款方式。


Enterprise Qualification/公司資質



**Business licence
營業執照**



**Trademark registration certificate
商標註冊證**



**Import and export license
進出口許可證**



IEC60335




IEC60950



IEC61558



UL/CUL



FCC



Doe VI



TUV/GS



TUV/CE




TUV/LVD



SAA



RCM



C-TICK




EMPS



TUV/PSE



TUV/PSB



CCC



KC



RoHS

電池充電器

Battery Charger

A

**Li-ion Battery
Charger**

B

**Lifepo4 Battery
Charger**

C

**Lead acid Battery
Charger**

D

**Lithium Titanate
Battery Charger**

E

**Ni-mh Battery
Charger**

電源適配器

Power Adapter

1

15W Series

2

24W Series

3

36W Series

4

65W Series

5

100W Series

6

135W Series

7

210W Series



Application / 產品應用







15W-24W Series Wall Plug

Specification:

1. AC input: 100-240V, 50/60hz.
2. Input current: 0.6A Max
3. DC output: 3V-48V, 0.3A-4A, 24W Max.
4. Ripple and noise: 70-100mV
5. Energy level: DoE VI, CEC VI, CoC V
6. AC Plug: US, EU, UK, AU, CN, JP, KR
7. Support interchangeable plug
8. Dimension: L72.3*W47.2*H30.5mm
9. Package: 100pcs/ctn, ctn size: L46*W29.5*H33CM



15W-24W系列 插牆式

規格參數：

1. AC輸入：100-240V, 50/60hz.
2. 輸入電流：0.6A 最大。
3. DC輸出：3V-48V, 0.3A-4A, 24W 最大。
4. 紋波：70-100mV。
5. 能耗等級：DoE VI, CEC VI, CoC V
6. AC 插腳：美規，歐規，英規，澳規，國標，日規，韓規等。
7. 支持可轉換插頭
8. 尺寸：L72.3*W47.2*H30.5mm
9. 包裝：100pcs/箱，外箱尺寸：L46*W29.5*H33CM





24W-36W Series Wall Plug

Specification:

1. AC input: 100-240V, 50/60hz.
2. Input current: 1.3A Max
3. DC output: 3V-58V, 0.3A-5A, 36W Max.
4. Ripple and noise: 85-120mV
5. Energy level: DoE VI, CEC VI, CoC V
6. AC Plug: US, EU, UK, AU, CN, JP, KR etc
7. Support interchangeable plug
8. Dimension: L91.8*W44.9*H37.5mm
9. Package: 100pcs/ctn, ctn size: L46*W29.5*H33CM



24W-36W系列 插牆式

規格參數：

1. AC輸入：100-240V, 50/60hz.
2. 輸入電流：1.3A 最大。
3. DC 輸出：3V-58V, 0.3A-5A, 36W 最大。
4. 紋波：85-120mV。
5. 能耗等級：DoE VI, CEC VI, CoC V
6. AC 插腳：美規，歐規，英規，澳規，國標，日規，韓規等。
7. 支持可轉換插頭
8. 尺寸：L91.8*W44.9*H37.5mm
9. 包裝：100pcs/箱，外箱尺寸：L46*W29.5*H33CM





C-6 C-8 Fixed

15W-24W Series Desktop

Specification:

1. AC input: 100-240V, 50/60hz.
2. Input current: 0.6A Max
3. DC output: 3V-48V, 0.3A-4A, 24W Max.
4. Ripple and noise: 70-100mV
5. Energy level: DoE VI, CEC VI, CoC V
6. AC inlet optional: IEC320-C6, C8, Fixed
7. Dimension: L87.8*W46.8*H31.5mm (Tab: 27mm)
8. Package: 50pcs/ctn, ctn size: L87.5*W46.8*H31mm




15W-24W系列 桌面式

規格參數：

1. AC輸入：100-240V, 50/60hz.
2. 輸入電流：0.6A 最大。
3. DC輸出：3V-48V, 0.3A-4A, 24W 最大。
4. 紋波：70-100mV。
5. 能耗等級：DoE VI, CEC VI, CoC V
6. AC 接口可選：梅花尾，八字尾或者兩頭出線。
7. 尺寸：L87.8*W46.8*H31.5mm (耳朵: 27mm)
8. 包裝：50pcs/箱，外箱尺寸：L87.5*W46.8*H31mm





24W-36W Series Desktop

Specification:

1. AC input: 100-240V, 50/60hz.
2. Input current: 1.3A Max
3. DC output: 3V-58V, 0.3A-5A, 36W Max.
4. Ripple and noise: 85-120mV
5. Energy level: DoE VI, CEC VI, CoC V
6. AC inlet optional: IEC320-C6, C8
7. Dimension: L99*W44*H31mm
7. Package: 50pcs/ctn, ctn size: L31.5*W31*H37CM



24W-36W系列 桌面式

規格參數：

1. AC輸入：100-240V, 50/60hz.
2. 輸入電流：1.3A 最大。
3. DC 輸出：3V-58V, 0.3A-5A, 36W 最大。
4. 紋波：85-120mV。
5. 能耗等級：DoE VI, CEC VI, CoC V
6. AC 接口可選：梅花尾，八字尾
7. 尺寸：L99*W44*H31mm
8. 包裝：50pcs/箱，外箱尺寸：L31.5*W31*H37CM





36W-65W Series Desktop

Specification:

1. AC input: 100-240V, 50/60hz.
2. Input current: 1.3A Max
3. DC output: 3V-58V, 0.3A-7.5A, 65W Max.
4. Ripple and noise: 100-120mV
5. Energy level: Doe VI, CEC VI, CoC V
6. AC inlet optional: IEC320-C6, C8, C14, Fixed
7. Dimension: L116*W52*H33.8MM
8. Package: 50 pcs/ctn, ctn size: L43*W38*H35CM



36W-65W系列 桌面式

規格參數：

- 1.AC輸入：100-240V, 50/60hz.
- 2.輸入電流：1.3A 最大。
- 3.DC 輸出：3V-58V, 0.3A-7.5A, 65W 最大。
- 4.紋波：100-120mV。
- 5.能耗等級：Doe VI, CEC VI, CoC V
- 6.AC接口可選：梅花尾，八字尾，品字尾或者兩頭出線。
- 7.尺寸：L116*W52*H33.8mm
- 8.包裝：50pcs/箱，外箱尺寸：L43*W38*H35CM





Product / 產品系列



C-6 C-8 C-14 Fixed

65W-100W Series Desktop

Specification:

1. AC input: 100-240V, 50/60hz.
2. Input current: 2.5A Max
3. DC output: 3V-58V, 0.3A-9A, 100W Max
4. Ripple and noise: 100-120mV
5. Energy level: DoE VI, CEC VI, CoC V
6. AC inlet optional: IEC320-C6, C8, C14, Fixed
7. Dimension: L137.61*W57*H34.5mm (Tab: 30mm)
8. Package: 48pcs/ctn, ctn size: L40*W34*H34CM



65W-100W系列 桌面式

規格參數：

1. AC輸入：100-240V, 50/60hz.
2. 輸入電流：2.5A 最大。
3. DC 輸出：3V-58V, 0.3A-9A, 100W 最大。
4. 紋波：100-120mV。
5. 能耗等級：DoE VI, CEC VI, CoC V
6. AC 接口可選：梅花尾，八字尾，品字尾或者兩頭出線。
7. 尺寸：L137.61*W57*H34.5mm (耳朵: 30mm)
8. 包裝：48pcs/箱，外箱尺寸: L40*W34*H34CM





C-6 C-8 C-14 Fixed

100W-135W Series Desktop

Specification:

1. AC input: 100-240V, 50/60hz.
2. Input current: 2.5A Max
3. DC output: 3V-73V, 0.3A-10A, 135W Max
4. Ripple and noise: 120-150mV
5. Energy level: DoE VI, CEC VI, CoC V
6. AC inlet optional: IEC320-C6, C8, C14, Fixed
3. Dimension: L151*W61*H39.2mm
4. Package: 42pcs/ctn, ctn size: L40*W34*H34CM



100W-135W系列 桌面式

規格參數：

1. AC輸入：100-240V, 50/60hz.
2. 輸入電流：2.5A 最大。
3. DC 輸出：3V-73V, 0.3A-10A, 135W 最大
4. 紋波：120-150mV。
5. 能耗等級：DoE VI, CEC VI, CoC V
6. AC 接口可選：梅花尾，八字尾，品字尾或者兩頭出線。
7. 尺寸：L151*W61*H39.2mm
8. 包裝：42pcs/箱，外箱尺寸:L40*W34*H34CM





C-6 C-8 C-14 Fixed

135W-210W Series Desktop

Specification:

1. AC input: 100-240V, 50/60hz.
2. Input current: 3A Max
3. DC output: 3V-73V, 0.3A-11A, 210W Max.
4. Ripple and noise: 120-150mV
5. Energy level: DoE VI, CEC VI, CoC V
6. AC inlet optional: IEC320-C6, C8, C14, Fixed
3. Dimension: L176*W80*H47mm
4. Package: 15pcs/ctn, ctn size: L45*W23.5*H29.5CM



135W-210W系列 桌面式

規格參數：

1. AC輸入：100-240V, 50/60hz.
2. 輸入電流：3A 最大。
3. DC 輸出：3V-73V, 0.3A-11A, 210W最大。
4. 紋波：120-150mV。
5. 能耗等級：DoE VI, CEC VI, CoC V
6. AC接口可選：梅花尾，八字尾，品字尾或者兩頭出線。
7. 尺寸：L176*W80*H47mm
8. 包裝：15pcs/箱，外箱尺寸：L45*W23.5*H29.5CM



Support ODM OEM
定制電源設計&制造



PCBA Open Frame
裸板

Military Class
Battery Charger
軍工級電池組充電器



AC/DC cord

Argentina 3P	Australia 3P	China 3P	European 3P	US 2P	Brazil 3P
					
Argentina 2P	Australia 2P	China 2P	European 2P	US Polarity 2P	Korea 2P
					
South Africa 3P	Japan 2P	Italy 3P	Israel 3P	US 3P	Switzerland 3P
					



UL LISTED FC CE CB TÜV GS TÜV PS ENEC CCC KC SAFETY DATA 123456-00 RoHS

Xinsu Global

Cooperated Partner / 合作的客戶

LISHEN

Honeywell

HIWIN
Motion Control and System Technology

 **BOSCH**

 **SUMITOMO**

ronda 朗达

partner^x



MTG
we have many dreams

TESCO

3M

Make practical and safe power supply.
Be enterprise with honesty and responsibility
做誠信負責的企業，提供實用安全的電源!



Contact us 聯繫我們

Add: 3rd Floor No.1 Building, Shenhuaye BaoAn Industrial Park, Xixiang
Western Development Zone, Baoan District,
Shenzhen City, Guangdong, China 518128

Tel: +86-0755-29706858

Fax: +86-0755-29706859

Email: info@xinsuglobal.com